

## AMENDMENTS TO THE CLAIMS

1. (Currently amended) A pipe joint, comprising:

a body part provided by rolling a planar material to form a cylindrical structure, the body part having a pair of opposing circumferential edges and a pair of opposing axial edges, the axial edges of the body part defining a longitudinal slot, the body part defining a central longitudinal axis extending between the pair of opposing circumferential edges, the body part further defining an axis transverse to the central longitudinal axis that extends between the pair of opposing axial edges of the body part;

a coupling part having a bent surface at opposing axial edges ~~each of both ends~~ of the body part, with a plurality of locking holes provided in ~~on~~ the bent surface of the coupling part;

locking means tightened into the locking holes to couple the opposing axial edges ~~both ends~~ of the body part to each other;

~~and~~ a reinforcing unit comprising a separate curved plate, the reinforcing unit having a pair of opposing circumferential edges and a pair of opposing axial edges, the reinforcing unit defining a longitudinal axis extending between the pair of opposing circumferential edges, the reinforcing unit further defining an axis transverse to the longitudinal axis that extends between the pair of opposing axial edges of the reinforcing unit, the reinforcing unit being gradually reduced in thickness along a circumferential direction extending its entire transverse axis from the its center of the reinforcing unit to both axial edges of the reinforcing unit to be in close contact with an inner surface of the body part; and

a positioning means comprising a linear ridge defined by the reinforcing unit that extends between the circumferential edges of the body part in a longitudinal direction along at least a portion of an outer surface of the reinforcing

unit, the linear ridge having a stepped shape that horizontally positions the reinforcing unit against the body part relative to the central longitudinal axis of body part, the stepped shape of the linear ridge extending outwardly from the interior of the body part and into at least a portion of the longitudinal slot of the body part to correspondingly engage the longitudinal slot;

wherein at least one edge of the pair of opposing circumferential edges of the body part and at least one edge of the pair of opposing circumferential edges of the reinforcing unit are ~~substantially~~ coplanar with respect to one another.

2. (Previously amended) The pipe joint according to claim 1, wherein the reinforcing unit further comprises:

a stop means having a stepped shape, the stop means extending along at least a portion of one edge of the pair of opposing circumferential edges of the reinforcing unit.

3. (Currently amended) The pipe joint according to claim 1, wherein the body part is stepped around a predetermined portion thereof so that upper and lower parts of the body part, relative to the central longitudinal axis thereof, differ in inner and outer diameters from each other, the upper part defined by an area between one of the circumferential edges of the body part and the stepped portion, and the lower part defined by an area between the other circumferential edge of the body part and the stepped portion, each of the upper and lower parts having a constant inner and outer diameter and defining substantially concentric, graduated parts such that the constant inner and outer diameter of one part is greater than the constant inner and outer diameter of the other part.

4. (Currently amended) The pipe joint according to any one of claims 1 through 3, further comprising:

a sealing unit provided for each of the body part and the reinforcing unit,  
the sealing units positioned against the radial interior surfaces of each of the body part and the reinforcing unit to provide a sealing effect after joining pipes.

5. (Previously amended) The pipe joint according to claim 4, wherein the sealing unit comprises:

a close contact means to increase a contact force at a contact surface thereof, the close contact means spaced apart and extending longitudinally along at least a portion of the surface of the sealing unit in contact with the inner surface of the body part.

6. (Original) The pipe joint according to any one of claims 1 through 3, wherein each of the coupling parts comprises a bending part to be attached to the body part.

7. (Cancelled).